

Simulating Complex Galaxy Images

Erin Sheldon

Brookhaven National Laboratory

December 6, 2016

Outline

- ▶ Why we want to test weak lensing codes with complex galaxies
- ▶ A new GalSim module
- ▶ Some pretty pictures

Weak Lensing Model Bias

- ▶ The ellipticity is a good shear estimator if the galaxy is well described by a single ellipse.
- ▶ Most real galaxies are not ellipses.



Real Galaxies



Real Galaxies



Real Galaxies



Real Galaxies



Real Galaxies



Real Galaxies



Real Galaxies



Real Galaxies



Real Galaxies



Weak Lensing Model Bias

- ▶ Most shear measurement algorithms fit some kind of simple elliptical model, and this results in “model bias”.
- ▶ Fitting more complex models is not possible: unstable
- ▶ With Metacalibration, we



Simulations


- ▶ Most common method to test model bias is to use HST images.
- ▶ Take real images, shear them, add extra noise, degrade psf
- ▶ This is very expensive

Alternate way: random walk

- ▶ Mentioned in Zhang et al. 2010 but with no details or code given; I implemented and added to Galsim
- ▶ Let a set of point sources take a “random walk” over the image
- ▶ Scale to requested scale radius and ellipticity
- ▶ Can represent an “irregular” galaxy, or can add to bulge+disk model to simulate knots of star formation.


Example Simulated Galaxies

Mostly bulge-like




Example Simulated Galaxies

Mostly disk-like




Example Simulated Galaxies

disk-like with some knots of star formation




Example Simulated Galaxies

disk-like with more knots of star formation



Example Simulated Galaxies

mostly irregular



Metacalibration

- ▶ I've been using these to test metacalibration
- ▶ Ten times faster than using HST images.
- ▶ So far metacal passes all tests.